

Safety and Inspections and Limitations:

- Discontinue use immediately if Any part of the bathtub or Accessory is damaged or broken or disassembled, or in any other position different from the instructions.
- Regularly inspect your baby bathtub for any signs of wear or damage.

Maintenance and Care:

- Ensure water temperature is between 90-100°F(32.2-37.8°C) before placing the infant in.
- Clean the bathtub after each use with a mild, baby-safe detergent and rinse thoroughly with warm water.
- Store in a dry cool place, away from direct sunlight

Never leave the infant unattended. For the safety of the child, it is crucial to always keep this product within arm's reach.

SAFETY WARNING!
(MUST READ)

- NOT A SAFETY DEVICE**
Babies have DROWNED while using bath seats.
- **Stay** in arm's reach of your baby.
 - **STOP** using when baby begins pulling to a standing position. Prevent drowning.
 - Babies can drown in as little as 1 inch of water. Use as little water as possible to bathe your baby.
 - **Never** rely on a toddler or preschooler to help your baby or alert you to trouble. Babies have drowned even when other children are in or near the bathtub.
- Additional warnings regarding suction cups and/or surfaces on which product is not intended for use.
- Not suitable for bathtubs with frosted particles or anti slip strips
- Use age suitable for babies 6-18 months

**DURING BATHING,
LET YOUR BABY FULLY
ENJOY IT ...**

St-down bath seat suitable for
babies 6-18 months



285x210mm

installation steps

- 1 Push down on the head accessory
- 2 Place the backrest on the back of the seat
- 3 Match armrest A with seat A
- 4 Match armrest B with seat B
- 5 Push armrest A into the clasp

installation steps

- 6 Push the B armrest into the clasp
- 7 Push the locking plate downwards to lock the armrest
- 8 Lift the locking plate upwards to open the armrest

sucker function introduction

Fixation and unlocking of the front suction cup

- 1 Press the button so that the suction cup holds the tub.
- 2 Lift the button up to remove the suction cup from the tub.

Fixation and unlocking of the posterior sucker

- 3 Position the bath chair on a flat and stable surface. Press firmly to the back suction cup so the rubber suction pad at the bottom can suction the bathtub, making it non-slip and stable.
- 4 Gently tug on the pull bars to separate the bathchair from the bathtub.

285x210mm